

## Typar® Construction Tape

### FOR COMMERCIAL AND RESIDENTIAL APPLICATIONS TYPICAL CHARACTERISTICS

Roll Dimensions	55 yards x 1 7/8" 16 rolls per carton
Peel Adhesion (PSTC*-1)	Immediate:
Typar	35 oz/in
Stainless steel	75 oz/in
Tensile Strength (PSTC-31)	20 lbs/in
Elongation	136%
Temperature Resistance:	
Minimum Application Temperature	0° F (-18° C)
Maximum use temperature	230° F (110° C)

#### \* Pressure Sensitive Tape Council

The information contained herein is to the best of our knowledge accurate and reliable and is provided for the user's assessment and verification. However, since the circumstances and conditions under which such information and the products discussed can be used may vary and are beyond our control, we make no warranty, expressed or implied, of merchantability, fitness or otherwise, or of the results to be obtained, or against patent infringement, and we disclaim all liability from any resulting damage or loss.

Typar®, Typar® Weather Protection System, and Typar® HouseWrap, are registered trademarks of Fiberweb, Inc.

Fiberweb, Inc., 70 Old Hickory Blvd., Old Hickory, TN 37138 USA, 1-800-284-2780 •  
Fax: 615-847-7068, [www.typar.com](http://www.typar.com)