

Typar® Flashing RA™ three part specs:

SPECIFICATIONS :

PART 1 - GENERAL

1.1 Section Includes

- A. Self-adhering Flashing (Typar Peel & Stick Flashing, Typar Flashing Flex and Typar Flashing RA).
- B. Primers.
- C. Fasteners.

1.2 References

- A. ASTM International
- 1. ASTM D-903, Standard Test Method for Peel or Stripping Strength of adhesive bonds.
- 2. ASTM D -2533, Standard practice for Twisting Load-Strain Properties.
- 3. ASTM D-1970, Standard Specification for Self-Adhesion polymer modified bituminous sheet materials.

1.3 Submittals:

- A. Product Data: Submit manufacturer current technical literature for each type of product.
- B. Submit copies of test results showing performance characteristics equaling or exceeding those specified.

1.4 Quality Assurance

A. Qualifications

- 1. Installer shall have documented successful experience with installation of TYPAR Flashing products.
- 2. Installation shall be in accordance with manufacturer's installation guidelines and recommendations.

PART 2 - PRODUCTS

2.1 Manufacturer

- A. Fiberweb, 70 Old Hickory Blvd, Old Hickory, TN 37138; 800-284-2780; www.typar.com

2.2 Materials

A. Self-adhering/straight flashing

a. Description

- i. Face material composition: smooth polypropylene barrier
- ii. Face color: gray
- iii. Adhesive composition: butyl adhesive
- iv. Thickness: 15mil
- v. Release liner: siliconized paper
- vi. Dimensions: 4 in. X 75 ft. 6 in. X 75 ft. 9 in. X 75 ft.

B. Self-adhering flashing flex

a. Description

- i. Face material composition: Conformable textured polyolefin
- ii. Face color: dark gray
- iii. Adhesive composition: butyl adhesive
- iv. Thickness: 60mil
- v. Release liner: siliconized paper
- vi. Dimensions: 6 in. X 75 ft. 9 in. X 75 ft.

C. Performance characterizations

- a. Low temp Flex ASTM D-903 PASS
- b. Nail sealability ASTM D-1970 PASS
- c. Tensile strength ASTM D-2523 PASS

2.3 Accessories

A. Primer: Use 3M-Super77- or equal

B. Seam tape: Typar construction

C. Fastener: Fastener is dependent on substrate construction

D. Sealant: Must comply with ASTM C920 elastomeric polymer sealant

PART 3 - EXECUTION

3.1 Examination

- A. Verify substrate and surface conditions are in accordance with the flashing manufacturer's recommendation.

NOTE - Flashing manufacturer recommends weather barrier be installed prior to the installation of the windows.

3.2 Installation

- A. Follow the Typar flashing installation procedures

3.3 Protection

- A. Protect installed flashing from damage during construction