

## Typar® Flashing RA™

### FOR COMMERCIAL AND RESIDENTIAL APPLICATIONS TYPICAL CHARACTERISTICS

Adhesive		Rubberized Asphalt
Recommended Exposure Limit		90 Days
Low Temperature Flexibility	(per ASTM D-146)	PASS
Nail Sealability	(per ASTM D-1970)	PASS
Tensile Strength	(per ASTM D-882)	11.6 lbs/inch

Roll sizes: 4 in x 75 ft, 6 in x 75 ft, 9 in x 75 ft and 12 in x 75 ft

The information contained herein is to the best of our knowledge accurate and reliable and is provided for the user's assessment and verification. However, since the circumstances and conditions under which such information and the products discussed can be used may vary and are beyond our control, we make no warranty, expressed or implied, of merchantability, fitness or otherwise, or of the results to be obtained, or against patent infringement, and we disclaim all liability from any resulting damage or loss.

Typar®, Typar® Weather Protection System, and Typar® HouseWrap, are registered trademarks of Fiberweb, Inc.

Fiberweb, Inc., 70 Old Hickory Blvd., Old Hickory, TN 37138 USA, 1-800-284-2780 •  
Fax: 615-847-7068, [www.typar.com](http://www.typar.com)