

TYPAR[®] FLANGEFLASH



FAST-FORWARD YOUR DOORS AND WINDOWS WITHOUT FLANGES.

Install the system. Get a lifetime limited warranty. TYPAR[®] FlangeFlash, along with the full TYPAR[®] Weather Protection System delivers unbeatable coverage.*

*Certain limitations and exclusions apply. See the TYPAR Weather Protection System Limited Warranty located online at TYPAR.com/downloads for full details.





TYPAR® FLANGEFLASH

NO FLANGES? NO COMPROMISES.

TYPAR FlangeFlash creates a self-adhered flange where none exists, forming a permanent mechanical bond between the window or door frame and the exterior wall. It simplifies this critical detail and provides a verifiable air and water barrier. This double-sided, self-sealing flashing tape combines the strength of TYPAR® Commercial with a high-performance, all-temperature adhesive. It's the only product of its kind providing 12 months of UV resistance and enabling year-round installation in temperatures down to 0° F. Count on rugged, lasting protection where it matters most.

LEADING FEATURES AND BENEFITS:

- Ideal for non-flanged doors and windows, as well as PTAC and VTAC units
- 12 months of UV resistance
- Self-sealing around nails, screws, and fasteners for a waterproof seal
- Clear adhesive eliminates messy residue
- Installs over wide temperature range (0° to 180° F / -18° to 82° C)
- No need for primers or adhesive
- Easy-release liner speeds installation
- Meets AAMA standard 711-13 for flashing tapes
- Lifetime limited warranty coverage*

INSTALL THE SYSTEM. GET A LIFETIME LIMITED WARRANTY.*

We're ready to take on your whole project. TYPAR FlangeFlash is part of the industry's most complete weather protection lineup that includes wraps, flashings, tapes, and more. All manufactured by us for true ruggedness and higher performance.

*TYPAR FlangeFlash is part of the TYPAR® Lifetime Limited System Warranty when used with the complete TYPAR® Weather Protection System. Certain limitations and exclusions apply. See the TYPAR Weather Protection System Limited Warranty located online at TYPAR.com/downloads for full details.

The information contained herein is to the best of our knowledge accurate and reliable and is provided for the user's assessment and verification. However, since the circumstances and conditions under which such information and the products discussed can be used may vary and are beyond our control, we make no warranties, express or implied, other than those warranties described in the TYPAR Weather Protection System Limited Warranty located online at TYPAR.com/downloads, subject to the limitations and exclusions described therein.

TYPICAL CHARACTERISTICS:

| | |
|--|-----------------------------|
| Facer | TYPAR Commercial |
| Adhesive | Block copolymer |
| Liner | Easy-release film |
| Thickness w/Release Liner | 24 mils |
| Application Temperature Range | 0°F (-18°C) to 180°F (82°C) |
| Ultraviolet Light Exposure Resistance | 12 months |
| Nail Sealability (ASTM D1970) | PASS |
| Peel Adhesion to Substrates (ASTM D3330) | |
| OSB | 4.0 lb/in |
| Plywood | 5.0 lb/in |
| Facer | 5.0 lb/in |
| ROLL SIZE (WITH LINER): | |
| 6" x 75' | |



October 2025 | Distributed in USA and Made with US and Global Components.
TYPAR® is a trademark of Magnera Corporation or one of its affiliates.
Please visit TYPAR.com for installation instructions and warranty information.
Building Wraps | Flashings | Construction Tape | Sealant

