

TYPAR® ALL-TEMPERATURE FLASHING TYPICAL CHARACTERISTICS

ALL-TEMPERATURE FLASHING

Characteristic	Test Method	Value
Nail Sealability	AAMA 711-13	Pass
90° Peel Adhesion	AAMA 711-13	
Plywood		5.0lb/in
OSB		3.8lbs/in
Facer		4.6lbs/in
Mold Growth	ASTM G-21	No Growth
Application Temperature		0°F to 180°F (-17.8°C to 82.2°C)

ROLL SIZES:	4" x 25'		6" x 75'		12" x 75'	
	Rolls/Case: 16	Cases/Pallet: 48	Rolls/Case: 8	Cases/Pallet: 48	Rolls/Case: 4	Cases/Pallet: 48
	4" x 75'		9" x 75'			
	Rolls/Case: 12	Cases/Pallet: 48	Rolls/Case: 4	Cases/Pallet: 48		

The information contained herein is to the best of our knowledge accurate and reliable and is provided for the user's assessment and verification. However, since the circumstances and conditions under which such information and the products discussed can be used may vary and are beyond our control, **we make no warranties, express or implied, other than those warranties described in the TYPAR® weather protection system limited warranty located online at <http://www.typar.com/downloads>, subject to the limitations and exclusions described therein.**



Made in USA. © 2025, Magnera Corporation.
TYPAR® is a registered trademark of Magnera Corporation or its affiliate.
Please visit [TYPAR.com](http://www.typar.com) for installation instructions and warranty information.
Building Wraps | Flashings | Construction Tape | Sealant

TYPAR®
A Magnera Brand