

TYPAR® FLANGEFLASH

TYPICAL CHARACTERISTICS

FOR COMMERCIAL AND RESIDENTIAL APPLICATIONS

Characteristic	Test Method	Value
Adhesive		Block Copolymer
Facer		TYPAR Commercial
Release Liner		Easy-Release Film
Thickness		24 mils (with release liner)
Ultra Violet Light Exposure Resistance (UV)		12 months
Nail Sealability	ASTM D1970	PASS
90° Peel Adhesion (lb/in)	D3330	
OSB		4.0
Plywood		5.0
Facer		5.0
Application Temperature Range		0°F (-17°C) to 180°F (82°C)
Shelf Life		24 Months

ROLL SIZE:

6" x 75'

Rolls/Case: 4

Cases/Pallet: 54

The information contained herein is to the best of our knowledge accurate and reliable and is provided for the user's assessment and verification. However, since the circumstances and conditions under which such information and the products discussed can be used may vary and are beyond our control. **WE MAKE NO WARRANTIES, EXPRESS OR IMPLIED, OTHER THAN THOSE WARRANTIES DESCRIBED IN THE TYPAR® WEATHER PROTECTION SYSTEM LIMITED WARRANTY LOCATED ONLINE AT [HTTP://WWW.TYPAR.COM/DOWNLOADS](http://www.typar.com/downloads), SUBJECT TO THE LIMITATIONS AND EXCLUSIONS DESCRIBED THEREIN.**



Made in USA. © 2025, Magnera Corporation.
 TYPAR® is a trademark of Magnera Corporation or an affiliate.
 Please visit [TYPAR.com](http://www.typar.com) for installation instructions and warranty information.
 Building Wraps | Flashings | Construction Tape | Sealant

TYPAR®
 A Magnera Brand