



DEFEND AGAINST EXCESS MOISTURE WITHOUT EXCESS EFFORT.

Install the system. Get a lifetime limited warranty.* TYPAR® DrainableWrap Peel and Stick, along with the full TYPAR® Weather Protection System, delivers unbeatable coverage.

'Certain limitations and exclusions apply. See the TYPAR Weather Protection System Limited Warranty located online at TYPAR.com/downloads for full details.





RAINABLEWRAP EELAND STICK

READY TO BEAT BULK WATER AND TIGHT TIMELINES?

Rely on our one-of-a-kind technology that gives enhanced drainability to our already superior weather barrier material. TYPAR DrainableWrap Peel and Stick is available in 4'10" rolls so you can cover more area than the average peel-and-stick quickly—without having to worry about which direction you're applying it. With the name TYPAR® comes market-leading trust in defending structures from the elements. And with the ability to peel, stick, and keep moving, comes an edge in staying on schedule.

LEADING FEATURES AND BENEFITS:

- · Delivers ease and speed of peel-and-stick installation
- · Provides the tear strength, air holdout, drainability, and breathability of TYPAR® DrainableWrap™
- · Drains significantly faster than conventional house wraps, per ASTM E2273 testing, with 94.8% efficiency
- · Reduces penetrations from fasteners to help create a tighter building envelope
- · Installs in any direction without affecting performance
- Offers improved cold temperature performance versus competition; installs down to 10°F (-12°C) without need of primer

INSTALL THE SYSTEM. GET A LIFETIME LIMITED WARRANTY.*

Our DrainableWrap Peel and Stick, along with our Flashings and Construction Tape, works as a part of the TYPAR® Weather Protection System. Install it all together and get the only lifetime limited warranty in the industry.

| TYPICAL CHARACTERISTICS: | | |
|---|-------------------|------------------------|
| Basis Weight | D5261 | 4.2 oz/yd² |
| Thickness | D1777 | 22.9 mils |
| Drainage Efficiency | E2273 | 94.8% |
| Peel Adhesion to Substrates: - OSB - Vinyl - Anodized - Plywood Aluminum | D3330 | >2 lbs/in |
| Cold Temperature Pliability | C765 | PASS |
| Breaking Strength (Grab Tensile) | D5034 | 67 lbs MD 73 lbs CD |
| Trapezoidal Tear Strength | D5733 | 30 lbs MD 33 lbs CD |
| Hydrostatic Pressure Resistance | AATCC 127-1995 | >500 cm |
| Moisture Vapor Transmission Rate | E96-95 | 10 perms |
| Ultraviolet Light Exposure Resistance | | 6 months |
| Air Permeance | E2178 | <.01 l/m² @ 75 Pa |
| Air Penetration Resistance (Gurley Hill Porosity) | | >2500 sec/ 100cc |
| Water Resistance Test | D779 | PASS |
| Surface Burning Characteristics (ASTM E84) | | |
| Flame Spread Index | | Class A |
| Smoke Spread Index | | PASS |
| ROLL SIZE: | | |
| 4' 10" x 100' | | |

*TYPAR DrainableWrap Peel and Stick is part of the TYPAR Lifetime Limited System Warranty when used with the complete TYPAR Weather Protection System. Certain limitations and exclusions apply. See the TYPAR Weather Protection System Limited Warranty located online at TYPAR.com/downloads for full details.

The information contained herein is to the best of our knowledge accurate and reliable and is provided for the user's assessment and verification. However, since the circumstances and conditions under which such information and the products discussed can be used may vary and are beyond our control, we make no warranties, express or implied, other than those warranties described in the TYPAR Weather Protection System Limited Warranty located on line at TYPAR. com/downloads, subject to the limitations and exclusions described therein.

NOTE: TYPAR DrainableWrap Peel and Stick is not available in Canada. ICC-ES #1404.





