




790

TYPAR Clear Flashing with Release Liner



- Backing:** Polypropylene
- Adhesive:** Acrylic
- Liner:** Backsplit Clear PET film
- Colors:** Clear with Black logo print
- Specifications:** AAMA 711-22 for Self-Adhering Flashing Used for Installation of Exterior Wall Fenestration Products
- Standard Sizes:** 4IN x 75FT, 6IN x 75FT, 9IN x 75FT, 12IN x 75FT

Applications

- Structural insulated sheathing (SISs) and Structural Insulated Panels (SIPs) seams
- Window & Door Installations
- Corner Board Abutments
- Sealing other detail areas against water and air penetration

Features

- Polypropylene Backing
- Acrylic Adhesive

Benefits

- Excellent conformability for bonding around curves and corners
- Durable and strong
- Self-sealing around screws
- Excellent cold-temperature adhesion
- Excellent adhesion to variety of substrates
- Provides permanent weather-tight seal on most clean, dry building surfaces
- Compatible with most sealants and caulking

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	9.5 mils	0.241 mm	ASTM D-1000
Adhesion to OSB	67 oz/in	7.33 N/cm	ASTM D3330 Method F 24h dwell, RT
Adhesion to Aluminum	144 oz/in	15.75 N/cm	ASTM D3330 Method F 24h dwell, RT
Adhesion to Vinyl	144 oz/in	15.75 N/cm	ASTM D3330 Method F 24h dwell, RT
Adhesion to Plywood	133 oz/in	14.55 N/cm	ASTM D3330 Method F 24h dwell, RT
Adhesion to Backing	38 oz/in	4.16 N/cm	ASTM D3330 Method F 24h dwell, RT
Tensile Strength	26 lb/in	45.53 N/cm	ASTM D3759 Procedure A
Elongation	707%		ASTM D3759 Procedure A
Installation Temperature	20 to 180 °F	-7 to 82 °C	
Operating Temperature	30 to 200 °F	-1 to 93 °C	
Shelf Life	36 Months		
UV Exposure	9 Months		

Recommended Storage Conditions: 60-80 °F at 40-60% RH
 Standard Shelf Life (at 25 °C): 36 months from date of manufacture.

The information contained herein is to the best of our knowledge accurate and reliable and is provided for the user's assessment and verification. However, since the circumstances and conditions under which such information and the products discussed can be used may vary and are beyond our control, we make no warranties, express or implied, other than those warranties described in the TYPAR Weather Protection System Limited Warranty located online at TYPAR.com/downloads, subject to the limitations and exclusions described therein.

