

# TYPAR® CLEAR ACRYLIC FLASHING

## TYPICAL CHARACTERISTICS

### FOR COMMERCIAL AND RESIDENTIAL APPLICATIONS

Characteristic	Test Method	Value
Adhesive		Acrylic
Facer		Polypropylene Film
Release Liner		Split back Film
Thickness		10 mils
Ultra Violet Light Exposure Resistance (UV)		9 months
Nail Sealability	ASTM D1970	PASS
Low Temperature Flexibility	ASTM D3330	PASS
Tensile Strength	ASTM D3759	30 lbs
Elongation	ASTM D3759	707%
90° Peel Adhesion (lb/in)		
OSB		4.2
Plywood		8.3
Aluminum		9
Vinyl		9
Operating Temperature		30°F (-1°C) to 200°F (93°C)
Shelf Life		36 Months

<b>ROLL SIZE:</b>	<b>4" x 75'</b>		<b>6" x 75'</b>	
	Rolls/Case: 12	Cases/Pallet: 27	Rolls/Case: 8	Cases/Pallet: 27
	<b>9" x 75'</b>		<b>12" x 75'</b>	
	Rolls/Case: 4	Cases/Pallet: 27	Rolls/Case: 4	Cases/Pallet: 27

The information contained herein is to the best of our knowledge accurate and reliable and is provided for the user's assessment and verification. However, since the circumstances and conditions under which such information and the products discussed can be used may vary and are beyond our control. **WE MAKE NO WARRANTIES, EXPRESS OR IMPLIED, OTHER THAN THOSE WARRANTIES DESCRIBED IN THE TYPAR® WEATHER PROTECTION SYSTEM LIMITED WARRANTY LOCATED ONLINE AT [HTTP://WWW.TYPAR.COM/DOWNLOADS](http://www.typar.com/downloads), SUBJECT TO THE LIMITATIONS AND EXCLUSIONS DESCRIBED THEREIN.**



1183\_0924

Made in USA. © 2024.  
Please visit [TYPAR.com](http://www.typar.com) for installation instructions and warranty information.  
Building Wraps | Flashings | Construction Tape | Sealant

