

# TYPAR® METROWRAP

## TYPICAL CHARACTERISTICS

### FOR COMMERCIAL APPLICATIONS

Characteristic	Test Method	Value
Thickness		12.1m
Base Weight	Tappi T-410	3.5oz/yd <sup>2</sup>
Breaking Strength (grab tensile)	ASTM D-5034 ASTM D-5034	93lbs MD 95lbs CD
Trapezoidal Tear Resistance	ASTM D-1117	60lbs MD 67lbs CD
Water Resistance Test	ATTC-127	>500 cm
Air Penetration Resistance	Tappi T-410	>4800 sec/100 cc
Water Vapor Transmission	ASTN E 96 Method A	10 Perms
Ultra Violet Light Exposure Resistance (UV)		12 Months
Surface Burning Characteristics Flame Spread Index Smoke Developed Index	ASTM E84	Class A PASS

ROLL SIZES:

**10' x 100'**

**5' x 150'**

The information contained herein is to the best of our knowledge accurate and reliable and is provided for the user's assessment and verification. However, since the circumstances and conditions under which such information and the products discussed can be used may vary and are beyond our control, **WE MAKE NO WARRANTIES, EXPRESS OR IMPLIED, OTHER THAN THOSE WARRANTIES DESCRIBED IN THE TYPAR® WEATHER PROTECTION SYSTEM LIMITED WARRANTY LOCATED ONLINE AT [HTTP://WWW.TYPAR.COM/](http://www.typar.com/) DOWNLOADS, SUBJECT TO THE LIMITATIONS AND EXCLUSIONS DESCRIBED THEREIN.**

ICC #ESR-1404 · CCMC #13286-R · CCMC #13289-R  
 Made in USA. © 2018, Berry Global, Inc.  
 TYPAR® is a registered trademark of Berry Global, Inc. or its affiliate.  
 Please visit [TYPAR.com](http://www.typar.com) for installation instructions and warranty information.  
 Building Wraps | Flashings | Construction Tape



4981

